

B.PRO
CATERING SOLUTIONS



TRAY TRANSPORT TROLLEYS

For safe and hygienic food distribution in the tray system.

GASTRO **ECONOMY**

Gastro Economy Sp. Jawna
ul. Zakopiańska 163a
30-435 Kraków

tel.: +48 12 260 26 40
e-mail: biuro@gastroeconomy.pl

STRONG SUPPORT

The tray transport trolleys from B.PRO Catering Solutions.



Superior appearance in an award-winning design: durable and high-quality with a perfect form.

Four ergonomic push handles with their large handle diameter make transport easier – regardless of which direction they're headed.

The extra-wide all-round bumper rail protects the trolley and furniture, as well as hands when pushing the unit through narrow corridors and doors.

The B.PRO tray transport trolleys (TTW) lend a supportive hand. The seamlessly deep-drawn support ledges help you load and unload trays swiftly. The four extra-long push handles offer an ergonomic handle height for everyone in the

team – for easier pushing, pulling, manoeuvring for persons of all sizes, even when the doors are open. The high-quality design ensures ideal hygiene with effortless cleaning, which saves valuable time.

**Quality that draws attention:
B.PRO tray transport trolleys –
for safe and hygienic food
distribution in the tray system.**

Convincing from the outside and the inside: Quality from the B.PRO brand.



High-quality materials

B.PRO tray transport trolleys are made of high-quality stainless steel (material 1.403). The micro polished surface is extremely resistant to soiling and germs.



Separate compartments

All doors can be opened independently of one another, even in the 3-door models. This facilitates removing the trays and helps to maintain constant temperatures in the interior for as long as possible.



Deep-drawn support ledges

Our deep-drawn ledge walls with integrated tip safety consist of a single piece – without dirty joints, sharp corners or edges. This makes cleaning easier, minimises the risk of injury and protects the trays.

COOL

B.PRO tray transport trolley with passive cooling

At B.PRO, the cooling elements are placed directly in the doors – simply insert the cooling elements (eutectic plates) in the holders on the inside of the doors, and you're done!

Because of this design principle, the interior is equipped entirely with closed ledge walls. Each compartment can be opened individually when loading and removing the trays.

What this means for customers: no undesired air exchange between the compartments, better temperature maintenance, fast access to the cooling elements, easier cleaning and better hygiene – because B.PRO always thinks ahead.



TTW-PK 20-115 DZE
Tray transport trolley, for passive
cooling with eutectic plates,
double-walled, insulated, for
Euronorm trays

B.PRO TRAY TRANSPORT TROLLEYS, FOR PASSIVE COOLING WITH EUTECTIC PLATES, DOUBLE-WALLED, INSULATED



For Euronorm trays	TTW-PK 16-115 DZE	TTW-PK 20-115 DZE	TTW-PK 24-115 DDE	TTW-PK 30-115 DDE
Model	Tray transport trolley, for passive cooling with eutectic plates, double-walled, insulated, for Euronorm trays			
Basic equipment	<ul style="list-style-type: none"> - Double-walled insulated, HS standard model in compliance with DIN 18865-9 - Holders on the inside of the doors for hanging in eutectic plates (<u>not</u> included in the scope of delivery) - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 2 fixed castors and 2 steering castors with brakes, galvanised steel 			
Eutectic plates	With 2 eutectic plates	With 4 eutectic plates	With 3 eutectic plates	With 6 eutectic plates
Hinged doors/compartments	2/2	2/2	3/3	3/3
Capacity	16 Euronorm trays, lengthwise	20 Euronorm trays, lengthwise	24 Euronorm trays, lengthwise	30 Euronorm trays, lengthwise
Space between ledges	115 mm	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	1122 x 783 x 1406 mm	1122 x 783 x 1636 mm	1554 x 783 x 1406 mm	1554 x 783 x 1636 mm
Weight (kg)	119 kg	133 kg	164 kg	179 kg
Order No.	573 722	573 725	573 728	573 731
For Gastronorm trays	TTW-PK 16-115 DZG	TTW-PK 20-115 DZG	TTW-PK 24-115 DDG	TTW-PK 30-115 DDG
Model	Tray transport trolleys, zur passiven Kühlung, double-walled, insulated, for Gastronorm trays			
Basic equipment	<ul style="list-style-type: none"> - Double-walled insulated, HS standard model in compliance with DIN 18865-9 - Holders on the inside of the doors for hanging in eutectic plates (<u>not</u> included in the scope of delivery) - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 2 fixed castors and 2 steering castors with brakes, galvanised steel 			
Eutectic plates	With 2 eutectic plates	With 4 eutectic plates	With 3 eutectic plates	With 6 eutectic plates
Hinged doors/compartments	2/2	2/2	3/3	3/3
Capacity	16 Gastronorm trays, lengthwise	20 Gastronorm trays, lengthwise	24 Gastronorm trays, lengthwise	30 Gastronorm trays, lengthwise
Space between ledges	115 mm	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	1032 x 783 x 1406 mm	1032 x 783 x 1636 mm	1419 x 783 x 1406 mm	1419 x 783 x 1636 mm
Weight (kg)	113 kg	125 kg	153 kg	171 kg
Order No.	573 734	573 737	573 740	573 743

B.PRO TRAY TRANSPORT TROLLEYS, FOR PASSIVE COOLING WITH EUTECTIC PLATES, DOUBLE-WALLED, INSULATED



For Euronorm or Gastronorm trays	TTW-PK 32-115 DZU	TTW 40-115 DZU
Model	Tray transport trolleys, for passive cooling with 2 eutectic plates, double-walled, insulated, for Euronorm or Gastronorm trays	Tray transport trolleys, for passive cooling with 3 eutectic plates, double-walled, insulated, for Euronorm or Gastronorm trays
Basic equipment	<ul style="list-style-type: none"> - Double-walled insulated, HS standard model in compliance with DIN 18865-9 - Model with dividing wall for the insertion of eutectic plates (not included in scope of delivery) - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 2 fixed castors and 2 steering castors with brakes, galvanised steel 	
Eutectic plates	With 2 eutectic plates	With 3 eutectic plates
Hinged doors/compartments	2/2	2/2
Capacity	32 Euronorm or Gastronorm trays, crosswise	40 Euronorm or Gastronorm trays, crosswise
Space between ledges	115 mm	115 mm
Dim. L x W x H (mm)	1452 x 956 x 1406 mm	1452 x 956 x 1636 mm
Weight (kg)	165 kg	180 kg
Order No.	574 894	574 895

B.PRO TRAY TRANSPORT TROLLEYS, **DOUBLE-WALLED, INSULATED**



For Euronorm trays	TTW 16-115 DZE	TTW 20-115 DZE	TTW 24-115 DDE	TTW 30-115 DDE
Model	Tray transport trolleys, double-walled, insulated, for Euronorm trays			
Basic equipment	<ul style="list-style-type: none"> - Double-walled insulated, HS standard model in compliance with DIN 18865-9 - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 2 fixed castors and 2 steering castors with brakes, galvanised steel 			
Hinged doors/compartments	2/2	2/2	3/3	3/3
Capacity	16 Euronorm trays, lengthwise	20 Euronorm trays, lengthwise	24 Euronorm trays, lengthwise	30 Euronorm trays, lengthwise
Space between ledges	115 mm	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	1122 x 783 x 1406 mm	1122 x 783 x 1636 mm	1554 x 783 x 1406 mm	1554 x 783 x 1636 mm
Weight (kg)	111 kg	124 kg	151 kg	166 kg
Order No.	573 721	573 724	573 727	573 730
For Gastronorm trays	TTW 16-115 DZG	TTW 20-115 DZG	TTW 24-115 DDG	TTW 30-115 DDG
Model	Tray transport trolleys, double-walled, insulated, for Gastronorm trays			
Basic equipment	<ul style="list-style-type: none"> - Double-walled insulated, HS standard model in compliance with DIN 18865-9 - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 2 fixed castors and 2 steering castors with brakes, galvanised steel 			
Hinged doors/compartments	2/2	2/2	3/3	3/3
Capacity	16 Gastronorm trays, lengthwise	20 Gastronorm trays, lengthwise	24 Gastronorm trays, lengthwise	30 Gastronorm trays, lengthwise
Space between ledges	115 mm	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	1032 x 783 x 1406 mm	1032 x 783 x 1636 mm	1419 x 783 x 1406 mm	1419 x 783 x 1636 mm
Weight (kg)	106 kg	118 kg	143 kg	159 kg
Order No.	573 733	573 736	573 739	573 742

PROTRAY TRANSPORT TROLLEYS, DOUBLE-WALLED, INSULATED



For Euronorm or Gastronorm trays	TTW 16-115 DEU	TTW 20-115 DEU	TTW 32-115 DZU	TTW 40-115 DZU
Model	Tray transport trolleys, double-walled, insulated, for Euronorm or Gastronorm trays			
Basic equipment	<ul style="list-style-type: none"> - Double-walled insulated, HS standard model in compliance with DIN 18865-9 - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 4 steering castors, 2 with brakes, galvanised steel 			
Hinged doors/compartments	1/1	1/1	2/2	2/2
Capacity	16 Euronorm or Gastronorm trays, crosswise	20 Euronorm or Gastronorm trays, crosswise	32 Euronorm or Gastronorm trays, crosswise	40 Euronorm or Gastronorm trays, crosswise
Space between ledges	115 mm	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	870 x 956 x 1406 mm	870 x 956 x 1636 mm	1452 x 956 x 1406 mm	1452 x 956 x 1636 mm
Weight (kg)	92 kg	102 kg	138 kg	158 kg
Order No.	573 745	573 747	573 749	573 751

DOUBLE-WALLED, INSULATED, HYGIENIC TYPE H1



For Euronorm or Gastronorm trays	TTW 16-115 DZE H1	TTW 20-115 DZE H1	TTW 40-115 DZU H1
Model	Tray transport trolleys, double-walled, insulated, double-walled, interior in hygienic type H1		
Basic equipment	<ul style="list-style-type: none"> - Double-walled, insulated, hygienic type H1 - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 2 fixed castors and 2 steering castors with brakes, galvanised steel 		
Hinged doors/compartments	2/2	2/2	2/2
Capacity	16 Euronorm trays, lengthwise insertion	20 Euronorm trays, lengthwise insertion	40 EN or GN trays, crosswise insertion
Space between ledges	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	1099 x 727 x 1314 mm	1099 x 727 x 1544 mm	1375 x 902 x 1544 mm
Weight (kg)	128 kg	141 kg	180 kg
Order No.	574 896	574 898	574 900

B.PRO TRAY TRANSPORT TROLLEYS, SINGLE-WALLED



For Euronorm trays	TTW 16-115 EZE	TTW 20-115 EZE	TTW 24-115 EDE	TTW 30-115 EDE
Model	Tray transport trolleys, single-walled, for Euronorm trays			
Basic equipment	<ul style="list-style-type: none"> - Single-walled HS standard model in compliance with DIN 18865-9 - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 2 fixed castors and 2 steering castors with brakes, galvanised steel 			
Hinged doors/compartments	2/2	2/2	3/3	3/3
Capacity	16 Euronorm trays, lengthwise	20 Euronorm trays, lengthwise	24 Euronorm trays, lengthwise	30 Euronorm trays, lengthwise
Space between ledges	115 mm	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	1122 x 783 x 1406 mm	1122 x 783 x 1636 mm	1554 x 783 x 1406 mm	1554 x 783 x 1636 mm
Weight (kg)	93 kg	103 kg	127 kg	141 kg
Order No.	573 720	573 723	573 726	573 729
For Gastronorm trays	TTW 16-115 EZG	TTW 20-115 EZG	TTW 24-115 EDG	TTW 30-115 EDG
Model	Tray transport trolleys, single-walled, for Gastronorm trays			
Basic equipment	<ul style="list-style-type: none"> - Single-walled HS standard model in compliance with DIN 18865-9 - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 2 fixed castors and 2 steering castors with brakes, galvanised steel 			
Hinged doors/compartments	2/2	2/2	3/3	3/3
Capacity	16 Gastronorm trays, lengthwise	20 Gastronorm trays, lengthwise	24 Gastronorm trays, lengthwise	30 Gastronorm trays, lengthwise
Space between ledges	115 mm	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	1032 x 783 x 1406 mm	1032 x 783 x 1636 mm	1419 x 783 x 1406 mm	1419 x 783 x 1636 mm
Weight (kg)	89 kg	98 kg	119 kg	134 kg
Order No.	573 732	573 735	573 738	573 741

B.PRO TRAY TRANSPORT TROLLEYS, SINGLE-WALLED





For Euronorm or Gastronorm trays	TTW 16-115 EEU	TTW 20-115 EEU	TTW 32-115 EZU	TTW 40-115 EZU
Model	Tray transport trolleys, single-walled, for Euronorm or Gastronorm trays			
Basic equipment	<ul style="list-style-type: none"> - Single-walled HS standard model in compliance with DIN 18865-9 - Deep-drawn support ledges with spacing of 115 mm - With 2 vertical, ergonomic push handles on the left and right of the short side - Rugged, all-round bumper rail - Castors with 160 mm dia., 4 steering castors, 2 with brakes, galvanised steel 			
Hinged doors/compartments	1/1	1/1	2/2	2/2
Capacity	16 Euronorm or Gastronorm trays, crosswise	20 Euronorm or Gastronorm trays, crosswise	32 Euronorm or Gastronorm trays, crosswise	40 Euronorm or Gastronorm trays, crosswise
Space between ledges	115 mm	115 mm	115 mm	115 mm
Dim. L x W x H (mm)	870 x 956 x 1406 mm	870 x 956 x 1636 mm	1452 x 956 x 1406 mm	1452 x 956 x 1636 mm
Weight (kg)	71 kg	79 kg	109 kg	129 kg
Order No.	573 744	573 746	573 748	573 750

ACCESSORIES

Illustration	Designation	For model	Order No.
	Eutectic plate (-12 °C), synthetic, Gastronorm-compatible	all TTW-PK	573 332
	Eutectic plate (-3 °C), synthetic, Gastronorm-compatible	all TTW-PK	568 136
not shown	Space between ledges 105 mm with tip safety , only for new orders, retrofitting not possible	all TTW (not possible with TTW-PK, TTW H1)	-
	Space between ledges 115 mm w/o tip safety, for compact trays , only for new orders, retrofitting not possible	TTW for EN trays; (not possible with TTW H1); TTW for EN and GN trays (not possible with TTW-PK U)	-
	Draw bar and coupling made of stainless steel , can be locked in place on short side. When ordering, please indicate whether draw bar on the left or right (only possible with castor arrangement A)	all TTW	-
not shown	Antistatic conveyor	all TTW	-
	Milled all-round bumper rail made of polyethylene	all TTW (not possible with TTW H1)	-
	Additional milled bumper rail on top	all TTW (not possible with TTW H1)	-
	All-round railing made of stainless steel, 50 mm high, with mitred welding	all TTW	-

Castors

Castor arrangement	Designation	For model
Castor arrangement A 	Galvanised steel castors, 160 mm dia. 4 steering castors, 2 with brakes	all TTW
	Galvanised steel castors, 200 mm dia. 2 fixed and 2 steering castors with brakes	all TTW
	Galvanised steel castors, 200 mm dia. 4 steering castors, 2 with brakes	all TTW
	Stainless-steel castors with elastic castors, 160 mm dia., either 2 fixed and 2 steering castors or 4 steering castors, 2 with brakes	all TTW
	Stainless-steel castors with elastic castors, 200 mm dia., either 2 fixed and 2 steering castors or 4 steering castors, 2 with brakes	all TTW
Castor arrangement D 	Stainless-steel castors with elastic castors, 160 mm dia., castor arrangement D: 4 steering castors in outer corners of trolley, 2 with central brake, 2 fixed rollers at centre lengthwise	TTW for EN trays; TTW for GN trays; TTW for 32/40 EN and GN trays
	Stainless-steel castors with elastic castors, 200 mm dia., castor arrangement D: 4 steering castors in outer corners of trolley, 2 with central brake, 2 fixed rollers at centre lengthwise	TTW for EN trays; TTW for GN trays; TTW for 32/40 EN and GN trays

THE B.PRO GROUP

Our customers are as diverse and varied as our portfolio. To ensure we do our very best for every client, we concentrate our skills, abilities and capacities in two highly specialised business units: B.PRO Catering Solutions – Products and systems for professional commercial kitchens. ENOXX Engineering – Custom-made high-precision pieces using stainless steel, aluminium or synthetics for industry.

All business units of B.PRO hold DIN EN ISO9001:2015 certification, guaranteeing a high standard of reliability and customer orientation.

B.PRO GmbH
B.PRO Catering Solutions
P.O. Box 13 10
75033 Oberderdingen
Germany
Phone +49 7045 44-81900
catering.export@bpro-solutions.com
www.bpro-solutions.com

B.PRO
CATERING SOLUTIONS

GASTRO ECONOMY

Gastro Economy Sp. Jawna
ul. Zakopiańska 163a
30-435 Kraków

tel.: +48 12 260 26 40
e-mail: biuro@gastroeconomy.pl